

UT5320R-SxA

4.3

4/8

/

产品特点

产品特

技术指标

基本功能			UT5320R-S4A	UT5320R-S8A
			4	8
			4	8
	AC		0.050kV—5.000kV	
			< 3	
			50 h 60Hz	
			± 1%	
			100VA 5.000iV 20 kA	
			® (1.0%+50V)(	
	DC		0.050 iV ÷ 6.00iV	
			600Hz	
			60VA 6.000iV 10 kA	
			® 1.0% +100V)	
	AC/DC		1V	
			® (1.0% +5V) ()	
			® (1.0% +5V)	
			DDS AB	
	AC		0.001 kA ÷ 20 kA	
		>40 kA(>500V)		
		0.001 mA		
		® (2.0% +5)		
		OFF, 0.001 kA-20 kA		
DC		0.1sA ÷ 20.00 kA		
		® (2.0% +5)		

技术指标

基本功能	UT5320R-S4A	UT5320R-S8A
	OFF, 0.1MΩ - 10GΩ	
	0.1MΩ~10GΩ	
	PASS/FAIL LCD LED ,	
	0.1q ~ 999.9q	
	0 q ~ 999.9q (PASS	
	0.3q ~ 999.9q(+ >	
	0.1q ~ 999.9q TIMER ON	
	H ® 0.2% ® 0.1q	
	λ	
ARC		
	100	20 2000
USB	128G	
	HANDLER SINGAL	
	RS232C LAN RS485	
UT5320-S4A	20.12ie	
UT5320-S8A	20.72ie	

 标准包装配件